

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 December 2005 (15.12.2005)

PCT

(10) International Publication Number
WO 2005/118405 A1

(51) International Patent Classification⁷: **B65B 65/00**,
E06B 7/23, F16J 15/46

[IT/IT]; Via Marconi, 41/A, I-40024 Castel S. Pietro Terme
(IT). **MARCHESCHI, Vittoriano** [IT/IT]; Via S. Gen-
naro, 68, I-55010 Lappato (IT).

(21) International Application Number:
PCT/IB2005/001312

(74) Agent: **LANZONI, Luciano**; Bugnion S.p.A., Via Goito,
18, I-40126 Bologna (IT).

(22) International Filing Date: 9 May 2005 (09.05.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
BO2004A000331 25 May 2004 (25.05.2004) IT

(71) Applicant (for all designated States except US): **I.M.A.
INDUSTRIA MACCHINE AUTOMATICHE S.P.A.**
[IT/IT]; Via Emilia Levante, 428-442, I-40064 Ozzano
Emilia (IT).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ,
OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL,
SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): **GASPERINI, Elvio**

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: A SEPARATION STRUCTURE FOR ISOLATING A DELIMITED SPACE FROM THE EXTERNAL ENVIRONMENT



(57) Abstract: A separation structure (1) for isolating a delimited space (B) from the external environment (A), in particular a space (B) defined by an apparatus operating in the pharmaceutical material processing sector, comprises suitably assembled separator means (2, 3, 4) of the panel type or the like and seal means (G) inserted between the separator means (2, 3, 4); the seal means (G) being of the fluid dynamic expansion type and formed by at least two separately expanding tubular ducts (6, 8; 13, 14; 5, 5'); in each of the two tubular ducts (6, 8; 13, 14; 5, 5') the supply of a pressurised or, if selected, negative pressure fluid being designed to be activated to cause the duct (6, 8; 13, 14; 5, 5') to expand or contract.